



Specifiche standard per tubi elettrolitici (0.20 ~ 3.0mm)

Unità: mm

Tubi in rame					Tubi in ottone					Coreless Tube				
Diametro esterno		Diametro interno			Diametro esterno		Diametro interno			Diametro esterno		Canali		Lungh. (mm)
Dia	Tol	S.T.	Tol	Lght	Dia	Tol	S.T.	Tol	Lgth	Dia	Tol	2	3	
0.20	+0	0.10	±0.01	300	0.20	±0.01	0.10	±0.01	400			2W		200
0.25		0.12			0.25		0.12							200
0.30		-0.01	0.20		0.30		+0	0.12						
0.40	+0	0.40			-0.01	±0.02	0.50	+0						
0.50		0.50			0.20			-0.01						
0.60		-0.02	0.30		0.60			±0.02						0.60
0.70	0.70				0.70									
0.80	0.80				0.80									
0.90	+0	±0.02	0.90		±0.02	0.90	+0	2W						
1.00			1.00			1.00								
1.10			1.10			1.10								
1.20	-0.02	0.40	1.20		±0.02	1.20	-0.02							
1.30			1.30			1.30								
1.40			1.40			1.40								
1.50	+0	±0.03	1.50		±0.03	1.50	+0	2T						3T
1.60			1.60	1.60										
1.70			1.70	1.70										
1.80	-0.03	0.50	1.80	±0.03	1.80	-0.03								
1.90			1.90		1.90									
2.00			2.00		2.00									
2.10	+0	±0.03	2.10	±0.03	2.10	+0								
2.20			2.20		2.20									
2.30			2.30		2.30									
2.40	-0.03	0.60	2.40	±0.03	2.40	-0.03								
2.50			2.50		2.50									
2.60			2.60		2.60									
2.70	+0	0.70	2.70	±0.03	2.70	+0								
2.80			2.80		2.80									
2.90			2.90		2.90									
3.00	-0.03	0.80	3.00	±0.03	3.00	-0.03								

Copper
300
Brass
400